

FIBER OPTIC TERMINATION BOX (ALUMINUM)

POLE & WALL Type

DESCRIPTION

The equipment is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.



FEATURES & BENEFITS

- Aluminum material housing for long product life
- Easy sliding way to open/close
- Water-proof, Dust-proof, Anti-aging, Protection
- Clamping the feeder cable and drop cable, fiber splicing, fixation, storage, distribution at once.
- Termination box can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses.



SPECIFICATION

Item	Specification
Insertion Loss	≤0.2 dB
Temperature Cycling	-40 to 60°C, 8 hours, 9 cycles
Salt spray	96 hours
Water Immersion	X, Y, Z, 3.8 L/min, 3 hours
Vibration	10-55-10 Hz, 3 hours

FIBER OPTIC TERMINATION BOX (ALUMINUM)

POLE & WALL Type

CONFIGURATION

Description	Size	Max Capacity		Cable entry
AI-OTP-A	241x358x70mm	SC	LC	Outdoor: 5ea Drop: 20ea
		16	32	

